



OmniStrap 380

BATTERY HANDTOOL
PLASTIC STRAP



The Cyklop OmniStrap 380 is the universal model in our range of cost effective battery operated strapping tools. Designed for simplicity and efficiency, the OmniStrap combines all essential strapping functions like tensioning, sealing, and cutting into one easy-to-use device. This all in one functionality simplifies the strapping process, reduces handling time, and increases overall efficiency on the job.

It features adjustable strap tension ranging from 250 to 4500 N, making it suitable for a wide variety of applications. This wide tension range allows the tool to be adapted to different packaging requirements and materials, making it suitable for use across a broad spectrum of industries from logistics and warehousing to manufacturing and distribution.

Compatible with both PET and PP strap widths of 12 to 16 mm, the OmniStrap offers flexibility for diverse packaging needs. Its battery-powered operation allows for full mobility, enabling use in multiple locations without dependence on external power sources. Weighing only 3.92 kg and ergonomically balanced, the tool ensures comfortable and quick operation for the user. Additionally, the device includes memory for five programmable settings, allowing consistent and efficient performance with every use.



EASY TO USE

- ✓ Touch Display
- ✓ Memory mode
- ✓ Strap alignment guides
- ✓ Welding time settings
- ✓ Tension force settings

IMPROVED PERFORMANCE

- ✓ Variable tension speed
- ✓ Tension indicator (filled out bars)
- ✓ Tension range with low mode
- ✓ More cycles per charge

FLEXIBLE & RELIABLE

- ✓ Save favorite settings
- ✓ For PP/PET strap
- ✓ For heavy and light packaged goods
- ✓ Display & audible signal
- ✓ Impact, dust, and moisture resistant



TECHNICAL DATA	
Strap	PP (Polypropylene) PET (Polyester)
Strap width	12 – 16 mm
Strap thickness	0.5 – 1.3 mm
Welding time	0.5 – 3.5 s
Tension force	250 – 4500 N
Tension speed	>200 mm/s
Weight	3.3 kg tool body 0.62 kg battery
Dimensions mm	L 352 x W 148 x H 156
Strapping cycles per charge	PP – 750 PET – 550
Battery	18V 5000 mAh